

WH-220

UNIVERSAL FUEL PUMP RELAY INSTALLATION INSTRUCTIONS

1. LOCATE THE RELAY ASSEMBLY CLOSE TO THE FUEL PUMP AND MOUNT WITH THE SCREW INCLUDED MAKING SURE TO ATTACH THE BLACK WIRE WITH THE RING TERMINAL TO CHASSIS GROUND AT THE SAME TIME.
2. MOUNT THE CIRCUIT BREAKER CLOSE TO THE POWER SOURCE.
3. ATTACH THE 12 GAUGE (LARGER) YELLOW/WHITE WIRE FROM THE RELAY TO THE FUEL PUMP.
4. ATTACH THE 18 GAUGE (SMALLER) YELLOW/WHITE WIRE TO A SWITCHED 12 VOLT SOURCE OR FUEL PUMP SWITCH, USING THE RED RING TERMINAL IF NECESSARY.
5. ATTACH THE RED 12 GAUGE WIRE TO THE CIRCUIT BREAKER AFTER CUTTING TO LENGTH, USING A YELLOW RING TERMINAL.
6. ATTACH THE REMAINING LENGTH OF RED WIRE BETWEEN THE BATTERY SOURCE AND THE UNUSED POST ON THE CIRCUIT BREAKER USING THE YELLOW TERMINAL PROVIDED.

